

TASKalfa 6501i

BLACK & WHITE MULTIFUNCTIONAL SYSTEM





- > Crisp Output up to 65 pages per minute
- > Color Scan Up to 100 ipm; B&W up to 180 ipm
- > Intuitive and Customizable Touch Screen Control Panel
- > Advanced Finishing Options to Power Workflow
- > Robust and Scalable Business Applications

- > Standard 270 sheet Dual Scan Document Processor
- > Statement 12" x 18" Printing from the Paper Trays
- > Tab printing available through multi purpose tray
- > Standard Searchable PDF capability
- > Apple AirPrint™ Enabled for a mobile printing solution



ONLY FROM KYOCERA

KYOCERA Document Solutions is a global leader in the digital imaging industry, with an award-winning line of document solutions that consistently set the standard for high performance, superior image quality, workflow-supportive applications, ease-of-use and durability. We get to the heart of your critical business challenges, with a personalized, single source approach that helps streamline your entire document workflow to reduce costs, increase workplace productivity and efficiency, and deliver exceptional results you can count on.

HARNESS THE POWER OF YOUR TASKalfa MFP WITH CUSTOMIZED BUSINESS APPLICATIONS



ACCUSENDER: Efficiently scan and distribute large files without unwanted size limitations.



PRESERVDOX: Securely augment business continuity



DMS LINK: Simplify document workflow through digital imaging, distribution, retrieval and long-time archival.



PINPOINT SCAN: Scan from your MFP to your PC with added speed, functions and versatility.



KYOCERA HOMEPOINT: Securely browse document folders from any networked KYOCERA MFP.

BASIC SPECIFICATIONS

Configuration: Black & White Multifunctional System – Print / Scan / Copy / Optional Fax

Pages Per Minute: Letter: 65 ppm; Legal: 39 ppm; Ledger: 32 ppm ; 12" x 18": 32 ppm (print only)

Warm Up Time: 30 Seconds or Less (Power On)

First Page Out:

Copy: 5.2 Seconds or Less; Print: 5.8 Seconds or Less **Resolution / Bit Depth:** 600 x 600 dpi; 9600 x 600 dpi interpolated / 8 bit depth

Memory / Hard Disk Drive: 3 GB RAM Standard / Dual 160 GB HDD or more

Duplex: Standard Stackless Duplex Supports Statement to 12" x 18", 16 lb Bond – 140 lb Index (60 – 256gsm)

Standard Output Tray:

Lower Tray: Statement - 12" x 18" / 250 sheets (80gsm), up to 12" x 48" Banner / Single Sheet Upper Tray: Statement - 12" x 18" / 100 sheets (80gsm) Right Tray: Statement - 12" x 18" / 70 sheets (80gsm)

Electrical Requirements: 120V, 60Hz, 16.0A; 220-240V, 50Hz, 9.5A Dimensions / Weight:

Footprint: 26.97" x 28.47" x 41.46";

with Control Panel: 40.91" x 28.47" x 53.03" / 341.72 lbs

Maximum Monthly Duty Cycle: 350,000 Pages Per Month

PAPER SUPPLY

Standard Paper Sources:

Dual 500 Sheet Trays, Dual 1,500 Sheet Trays, 150 Sheet MPT; Auto Selection/Switching

Optional Paper Sources:

Side LCTs: 500 Sheet Multi-Media Tray (PF-780(B)) + Dual 500 Sheet Trays (PF-730(B)) or Dual 1,500 Sheet Trays 8.5" x 11" (PF-740(B)); 3,000 Sheet Large Capacity 8.5" x 11" Tray (PF-770)

Paper Capacity:

Standard: 4,150 Sheets; Maximum: 7,650 Sheets

Paper Size: Trays 1, 2, PF-730(B), PF-780(B): 5.5" x 8.5" – 12" x 18"; Trays 3, 4, PF-740(B), PF-770: 8.5" x 11"; MPT: 5.5" x 8.5" – 12" x 18" (Multiple Sheets)

Paper Weight:

Trays: 16 lb Bond – 140 lb Index (60 – 256gsm); MPT: 16 lb Bond – 110 lb Cover (60 – 300gsm)

Input Materials:

Bond Paper, Recycled Paper, Transparencies, Cardstock, Envelopes, Labels / Tabs

SECURITY SPECIFICATIONS

Standard: Local Authentication, Network Authentication (IPsec, HTTPS, LDAP over SSL, SMMPv3); Secure Print (IPP over SSL); Scan to e-mail (POP3/SMTP over SSL); Scan to FTP (FTP over SSL); Scan to SMB/PC/USB; SSL

Optional: Data Security Kit (E): Network Data Encryption, HDD Overwrite Mode, HDD Data Encryption

PRINT SPECIFICATIONS

Standard Controller: Freescale QorlQ P1022 (Dual Core) 1,067MHz
PDLs / Emulations: PRESCRIBE, PCL6 (5e, XL), KPDL3 (PS3), XPS;
Optional (UG-34): IBM ProPrinter, Line Printer, LQ-850
Fonts: 136 KPDL3. 93 PCL6. 8 Windows Vista. 1 Bitmap

Windows® OS Compatibility: Windows XP/2003/Vista/2008/7/8 Server 2008 R2 / Server 2012

Novell OS Compatibility: Novell NetWare 3.x/4.x/5.x/6.x Mac OS Compatibility: Mac OS 10.x, AirPrint Enabled

UNIX OS Compatibility: Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)

Interfaces: Standard: 10/100/1000BaseTX, Hi-Speed USB 2.0, 4 USB Host Interfaces, 2 Expansion Slots; Optional: 10/100/1000BaseTX (IB-50 for Dual NIC); Optional: IEEE 802.11 b/g/n (IB-51 for Wireless LAN Interface)

Network Print and Supported Protocols:

TCP/IP, NetBEUI, FTP, LPR, IPv6, IPsec, SSL, WSD Print

Drivers: KX Driver, Mini Driver, KX Driver for XPS, XPS Mini Driver, Network Fax Driver, PPD for MAC

Utilities: KYOCERA Net Admin, KYOCERA Net Viewer, PDF Direct Print, Command Center RX

SCAN SPECIFICATIONS

Scan Type: Color and Black & White Scanner

Scan Resolution: 600 dpi, 400 dpi, 300 dpi, 200 dpi, 200 x 100 dpi, 200 x 400 dpi

File Formats: Black and White: TIFF, XPS, PDF, PDF/A;

Color: TIFF, JPEG, XPS, PDF, PDF/A

PDF Extension: High Compression PDF, Encrypted PDF, Searchable PDF (OCR)

Scan Speeds

Simplex: 100 ipm BW, 70 ipm Color (300 dpi); Duplex: 180 ipm BW, 100 ipm Color (300 dpi)

Connectivity / Supported Protocols: 10/100/1000BaseTX, TCP/IP Scanning Functions: Scan to Folder (SMB), Scan to e-Mail, Scan to FTP, Scan to FTP over SSL, Scan to USB, WSD Scan, TWAIN Scan

Original Size: Through DP: Statement to 11" x 17"; Glass: up to 11" x 17" $\,$

Driver: TWAIN/WIA Driver

COPY SPECIFICATIONS

Image Mode: Text, Photo, Text/Photo, Auto, Manual, Map

Continuous Copy: 1 – 9,999 / Auto Reset to 1

Additional Features: Positive/Negative Reverse, Mirror Image, Rotate Copy, Border Erase, Split Copy, Electronic Sort, Margin Shift, Page Number, Form Overlay, XY Zoom, Prevent Bleed Through, Text Stamp, Bates Stamp, Blank Page Skip

Job Management: 1,000 Department Codes, Job Programs, Job Build, Shortcut Keys, Repeat Copy

Magnification / Zoom: Full Size, 4 Reduction, 4 Enlargement Preset Ratios, 25 – 400% in 1 step increments

Document Box: Custom Box, Job Box, Removable Memory Box, Fax Box (with optional Fax System)

DOCUMENT PROCESSOR

Type / Capacity: Standard Dual Scan Document Processor / 270 Sheets

Acceptable Originals: 5.5" x 8.5" – 11" x 17" Acceptable Weights (Simplex / Duplex): Simplex: 9.5 lb Bond – 80 lb Cover; (35 – 220gsm) Duplex: 13 lb Bond – 80 lb Cover (50 – 220gsm)

FAX SPECIFICATIONS

Fax Type: Fax System W(B) / Internet Fax Kit (A) (requires Fax System W(B))

Compatibility / Data Compression: G3 Fax / MMR, MR, MH, JBIG Transmission Speed / Modem Speed: Approximately 3 seconds per page / 33.6 Kbps

Fax Transmission Selection: Normal/Fine/SuperFine/Ultra Fine

Fax Memory: Standard: 12 MB; Maximum: 120 MB

Driver: Network Fax Driver

Fax Functions: Duplex TX/RX, Confidential RX/TX, F-Code RX/TX, Broadcasting, Fax Box, Dual Fax

OPTIONAL 4,000 SHEET FINISHER DF-790(C)

Stack / Staple Capacity: Main Tray: 4,000 Sheets; Sub Tray (B): 200 Sheets; Sub Tray (C): 100 Sheets / 65 Sheets (up to 24 lb Bond (90gsm))

Paper Size: 5.5" x 8.5" - 12" x 18"

Paper Weight: 16 lb Bond - 110 lb Cover (60 - 300gsm)

Edge Staple Position: 3 Positions: Top Left, Bottom Left, Center Bind Optional Multi-bin Mailbox: MT-730(B) Includes 7 Trays; Supports 16 lb Bond – 90 lb Index (60 – 163gsm) Stack Capacity per bin: 100 Sheets: 5.5" x 8.5", 8.5" x 11"; 50 Sheets: 8.5" x 14", 11" x 17"

Optional Punch: PH-7A 2 and 3 Hole Punch Unit, Supports 8.5" x 11" – 12" x 18"; 13 lb Bond – 110 lb Cover (45 – 300gsm)

Optional Booklet Folder / Tri-fold Unit: BF-730 Booklet Folder Supports 8.5" x 11", 8.5" x 14", 11" x 17"; 16 lb Bond -24 lb Bond $(60-90\mathrm{gsm})$ 16 sheets; 25 lb Bond -28 lb Bond $(91-105\mathrm{gsm})$ 13 sheets; fold booklet - no staple: 16 lb Bond -24 lb Bond $(60-90\mathrm{gsm})$ 5 sheets; 25 lb Bond -72 lb Index $(91-120\mathrm{gsm})$ 3 sheets; 32 lb Bond -110 lb Cover $(121-256\mathrm{gsm})$ 1 sheet; Trifold: 16 lb Bond -24 lb Bond $(60-90\mathrm{gsm})$ 5 sheets; 25 lb Bond -72 lb Index $(91-120\mathrm{gsm})$ 3 sheets

ADDITIONAL OPTIONS

Data Security Kit Provides Security Overwrite and Encryption for Print, Copy, and Scan, Optional Fax Memory, Original Hardcopy Holder (Document Tray), Card Authentication Kit (B), Banner Guide (A), Keyboard Holder (C)

Specifications and design are subject to change without notice. For the latest on connectivity visit www.kyoceradocumentsolutions.com/us DMS Link, PinPoint Scan, AccuSender and PreservDox are trademarks of the KYOCERA Companies.

MAC and AirPrint are trademarks of Apple, Inc. Other trademarks are the property of their respective owners.

KYOCERA Document Solutions America, Inc.
Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA
©2013 KYOCERA Document Solutions America. Inc.













