

TECHNOLOGY



# **bizhub<sup>®</sup> C659** COLOR HIGH-VOLUME MULTIFUNCTION PRINTER

Up to 65 ppm print/copy output to keep pace with rising demands
Standard dual scanning handles up to 240 originals per minute
High capacity 300-sheet document feeder
Large 10.1" color display with quick tablet-like touchscreen interface
Scan-to-email and FTP, scan-to-me, scan-to-home convenience
Built-in Emperon <sup>®</sup> print system, universal printer drivers
Simitri <sup>®</sup> HD polymerized toner for high-resolution imaging
Standard 250 GB HDD for on-board document storage
Web browser with 4 GB of memory
ISO 15408 and IEEE 2600.1 security standards

Power-saving design with quick recovery from sleep mode
6,650-Sheet maximum capacity, tab printing support, carbon-copy printing
Advanced authentication, secure print release, remote firmware updates
Multiple bypass tray and detachable paper feed trays improve paper handling
Finishing options for 80-page booklet-making, up to 100-sheet stapling
Options for 2/3-hole punch, tri-fold, z-fold, post-insertion and more
Downloadable apps to help you work faster and smarter
Multiple i-Options to suit the needs of your workflow
EPEAT Gold-certified, low power consumption to cut costs
Mobile printing support (AirPrint, Google Cloud Print Classic, NFC)

## bizhub C659

### COLOR HIGH-VOLUME MULTIFUNCTION PRINTER

Superior color, spectacular speed and simple touch-and-swipe operation make the bizhub C659 an ideal document solution for high-volume applications. Output speeds of 65 ppm plus duplex scanning at up to 240 opm keep work flowing — and you'll have powerful, scalable options to increase your productivity and help control your costs.

### SYSTEM OVERVIEW

System memory	4 GB
System hard disk	250 GB Standard
Interface	10-BASE-T / 100-BASE-TX / 1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB v2, LPD, IPP, SNMP, HTTP
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Dual scan	Up to 300 originals / 5.5" x 8.5" to 11" x 17" / 35-210 gsm
document feeder	
Printable paper size	Scanning/Copying: up to 11" x 17"
	Printing: up to 11" x 17" full bleed on 12" x 18" paper
	Custom paper sizes
	Banner paper max.: 11.75" x 47.25"
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 3,650 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3	1,500 sheets / 5.5" x 8.5", 4" x 6" / 52-256 gsm
Tray 4	1,000 sheets / 5.5" x 8.5", 4" x 6" / 52-256 gsm
Large capacity tray	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
LU-205 (optional)	
Large capacity tray	3,000 sheets / 8.5" x 11" / 52-256 gsm
LU-303 (optional)	
Manual bypass	150 sheets / 4" x 6" to 12" x 18" /
	custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, sort, staple, punch, half-fold, z-fold, tri-fold,
	post-insertion, booklet
Output capacity	Max. with finisher: 3,300 sheets
	Max. without finisher: 250 sheets
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheets (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray)
Copy/print volume	Max.: 300,000 pages / month <sup>1</sup>
Toner lifetime	Black: 48,900 pages / CMY: 33,200 pages
Imaging unit lifetime	Black: 300,000 pages / 1,200,000 pages (Drum/Developer)
	CMY: 200,000 pages
Power consumption	120 V / 60 Hz, less than 2.1 kW (system)
System dimensions	25.5" x 31.5" x 45.5" (W x D x H)
System weight	Approx. 487 lb.

COPIER SPECIFICATIONS	
Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri <sup>®</sup> HD Polymerized Toner
Print speed (8.5" x 11")	B&W / Color: up to 65 / 65 ppm (Portrait)
Print speed (11" x 17")	B&W / Color: up to 33 / 33 ppm (Portrait)
Autoduplex speed	B&W / Color: up to 65 / 65 ppm (Portrait)
(8.5" x 11")	
1st copy out time	B&W: 3.7 sec. / Color: 4.9 sec.
Warm-up time	B&W: approx. 22 sec. <sup>2</sup> / Color: 35 sec. <sup>2</sup>
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1-9,999
Original format	Up to 11" x 17"
Magnification	25-400% in 0.1% steps, auto zooming
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness
	image density), proof copy, interrupt mode, color mode,
	separate scan, sort/group, combination, original selection,
	ID card copy, 2-in-1, 4-in-1
PRINTER SPECIFICATION Print resolution	1,800 (equivalent) x 600 dpi, 1,200 x 1,200 dpi
PDL	PCL6 (XL 3.0), PCL5e/c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32 / x64): 7 / 8 / 10
operating systems	Windows (x32 / x64): 7 / 87 10 Windows Server (x32 / x64): 2008 / 2008 R2 <sup>3</sup> / 2012 <sup>3</sup> / 2016 <sup>3</sup>
	Macintosh OS X 10.8 or later
	Linux / Unix / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and
	OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy
	Set" job programming, overlay, watermark, copy protection,
	carbon copy print
<b>PRINTER SPECIFICATION</b>	S (OPTIONAL)
Print controller	Embedded Fiery IC-418 (VI-510 required)
Memory/HDD	4 GB / 250 GB
PDL	PostScript 3 (ver. 3019)
	PCL 6 / 5c
Operating systems	Windows (x32 / x64): 7 / 8 / 10
	Macintosh OS X 10.7 or later
SCANNER SPECIFICATIO	8
Scan speed	B&W / Color: up to 240 ipm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-
Scall modes	to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scar
File formats	IPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF,
	encrypted PDF and searchable PDF (optional), XPS, compact
	XPS, PPTX and searchable PPTX (optional), searchable DOCX/
	XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs,
	real-time scan preview
FAX SPECIFICATIONS	
Fax	Super G3 (optional)
Transmission	Analog, Internet fax, Color i-Fax, IP-Fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt
	to Email/FTP/SMB, up to 400 job programs
USER BOX SPECIFICATIO	
USER BOX SPECIFICATIO Storable documents Type of user boxes	Max.: 3,000 documents or 10,000 pages Public

ijpe ei acei nektee	1 4510
	Personal (with password or authentication)
	Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation
User box functionality	Reprint, combination, download, sending (Email/FTP/SMB and
	fax), copy box-to-box

Security	ISO 15408 EAL34
•	IEEE 2600.14
	IP filtering and port blocking
	SSL2, SSL3 and TSL1.0 network communication
	IPsec support
	IEEE 802.1x support
	FIPS 140-2
	User authentication
	Authentication log
	Secure print
	Hard disk overwrite (8 standard types)
	Hard disk data encryption (AES 128)
	Memory data auto deletion
	Confidential fax receipt
	Print user data encryption
	Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts
	Active Directory support
	(user name + password + Email + SMB folder)
	User function access definition
	Optional Biometric authentication (finger vein scanner)
	Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility
	Log Management Utility

<sup>1</sup> Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.
 <sup>2</sup> Warm-up time may vary depending on the operating environment and usage.
 <sup>3</sup> Supports x64 only.
 <sup>4</sup> Certification pending.


### COMPONENTS AND OPTIONS

AU-102 Biometric authentication	Finger vein scanner
AU-205H Universal	Various ID card technologies
ID card reader	
AU-211	Requires WT-506 Working Table
CAC/PIV solution*	
EK-610 USB I/F kit	USB keyboard connection
EK-611 USB I/F kit	USB keyboard connection, Bluetooth
FK-516 Fax board	Super G3 fax, digital fax functionality
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support (requires MK-742)
FS-536 Staple finisher	50-sheet stapling, 3,200 sheets max. output
FS-536SD	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	2,500 sheets max. output
FS-537 Staple finisher	100-sheet stapling, 3,200 sheets max. output
FS-537SD	100-sheet stapling, 20-sheet booklet finisher,
Booklet finisher	2,500 sheets max. output
HD-524 Hard disk	Backup HDD
IC-418 Fiery image	Embedded image controller for graphics-intensive applications
controller	
JS-602 Job separator	Separation for fax output, etc.
for FS-537	
Keyboard	External keyboard (requires KH-102)
KH-102	To place USB keyboard
Keyboard holder	
KP-101 10-Key pad	For use instead of touchscreen
LK-102 v3	PDF/A, PDF encryption, digital signature
LK-104 v3	Provides voice guidance functions
LK-105 v4	Searchable PDF
LK-106	Supports native barcode printing

COMPONENTS AND OPT	
LK-107	Supports native Unicode printing
LK-108	Supports native OCR A and B font printing
LK-110 v2	Generates various file formats incl. DOCX, XLSX and
	combines LK-102 (encrypted PDF) + LK-105 (searchable PDF/
	OCR functionality)
LK-111	ThinPrint <sup>®</sup> Client data compression for
	reduced network impact
LU-205	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
Large capacity unit	
LU-303	3,000 sheets / 8.5" x 11" / 52-256 gsm
Large capacity unit	
MK-715 Mount kit	Banner paper guide
MK-735 Mount kit	Installation kit for ID card reader
MK-742 Mount kit	Installation kit for FK-515 fax board
OT-508 Output tray	Output tray used instead of finisher
PI-507 Post inserter	Cover insertion, post finishing
for FS-537	
PK-520 Punch kit	2/3-hole punching, autoswitching
for FS-536	
PK-523 Punch kit	2/3-hole punching, autoswitching
for FS-537	
RU-515 Relay unit	Required for FS-537/FS-537SD and FS-536/FS-536SD
SC-508 Security kit	Copy Guard function (2x required)
SK-602 Staple kit	Added stapling functionality kit
SP-501 Stamp unit	Added fax stamp capability kit
UK-212 Wireless LAN	Wireless LAN to network connector
UK-501 Multi-feed	Detects multi-feeding in the document feeder
detection kit	····· 5
VI-510 Interface kit	Fiery controller interface card
for IC-418	
WT-506 Working table	Authentication device placement
WT-513 Upright	Required to mount the control panel in an upright position,
working table	can also be used to hold authentication devices
ZU-609 Z-fold unit	Z-fold for 11" x 17" prints
for FS-537	r
* May not be available at time	oflaunch

\* May not be available at time of launch.





## PARTNERSHIP

Konica Minolta can help give shape to your ideas and partner with you to achieve your corporate objectives. Contact us to realize opportunities in:

**IT SERVICES** 

#### **INFORMATION MANAGEMENT**

Enterprise Content Management (ECM) Document Management Automated Workflow Solutions Business Process Automation Security and Compliance Mobility eDiscovery Services

#### TECHNOLOGY

Application Services Cloud Services IT Security Managed IT Services IT Consulting & Projects Business Consulting Services

## Office Multifunction Business Solutions Commercial and Production Printers 3D Printers Wide Format Printers Laptops, Desktops and Computer Hardware Servers and Networking Equipment Managed Print Services (MPS) Managed Enterprise Services



For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2017 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com



Item #: C659SS 12/2017-C