


Highly efficient MFP for your business needs

Designed to operate in demanding high-end work environments and keep up with your ever-changing way of working. These user friendly, secure and productive B/W MFP series — TASKalfa 7003i, 8003i and 9003i — will astonish you. Thanks to its newly designed 10.1" touch panel, accessing all features and getting exactly the results you need, is very intuitive and simple. To keep your data safe these models are equipped with various security features. In addition, the maximum input paper capacity of 7,650 sheets and output paper capacity of 4,300 sheets, is well suited to handle your largest and most complex print jobs.



Specifications

GENERAL

KYOCERA TASKalfa Laser Black & White Multifunctional, HyPAS™ solution platform

Operation panel: 256.5 mm (10.1 inch) full-colour touch panel display, speaker for job notification, 15°-90° swivel mounted display, speaker for job notification, 15'—90' swivel mounted Engine speed: Up to 70 pages A4 per minute, Up to 35 pages A3 per minute, Duplex print speed: 70 pages per minute, A4 Resolution: 1,200 × 1,200 dpi (print), 600 × 600 dpi (scan/copy) Warm-up time: Approx. 30 seconds or less from power on

Time to first print: Approx. 4.8 sec. or less
Time to first copy: Approx. 4.2 sec. or less (DP)
CPU: NXP QorlQ T1024 (Dual Core) 1.4 GHz
Memory: Standard 4.5 GB, Max. 8 GB SSD + 320 GB HDD

Standard interfaces: USB 2.0 (Hi-Speed), 4 × USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPSec, 802.3az support), NFC tag, 2 eKUIO slots for optional internal print server or for optional fax system(s), slot for optional SD Card

Integrated accounting: 1,000 department codes **Dimensions (W** \times **D** \times **H):** 750 mm \times 822 mm \times 1,234 mm Weight: Main unit approx. 150 kg

Power source: AC 220–240 V, 50/60 Hz Power consumption: Print mode: 1110 W, Copy mode: 1110 W, Low power mode: 100 W, Ready mode: 110 W, Sleep mode: 0.7 W Noise (sound pressure level ISO 7779 measurement distance of 1 meter): Copying/Printing: 54,2 dB(A) L_{pA}, Stand by mode: 33,8 dB(A) L_{pA}

Safety standards: TÜV/GS, CE; This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

er capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: Multi-purpose tray: 150 sheets, 60-300 g/m² (Banner 136–165 g/m²), А3+, А3, А4, А5, А6, В5, Ledger, Letter, Legal, Folio, Custom (98 × 148 to 297 × 432 mm), Banner max. 305 × 1,220 mm;

Standard universal paper cassette: 2×500 sheets, 60-256 g/m², A3+, A3, A4, A5, B5, Ledger, Letter, Legal, Folio;

High-capacity paper deck: $2\times1,500$ sheets, 60-256 g/m², A4, B5. Max. input capacity with options: 7,650 sheets A4

Document processor: (one-path duplex scanning) 270 sheets. 35–220 g/m² (simplex), 50–220 g/m² (duplex), A6R–Banner up to 2,200 mm

Duplex as standard unit: 60-256 g/m², A5R-305 × 457 mm Output capacity: Standard job separator tray 70 sheets; optional copy tray (D): upper 100 sheets, lower 250 sheets; max. optional output capacity 4,300 sheets

PRINT FUNCTIONS

Controller language: PRESCRIBE

Emulations: PCL6 (PCL-XL/PCL-5e), KPDL 3 (PostScript 3 compatible), PDF, XPS/OpenXPS, PPML

Operating systems: All current Windows operating systems, MAC OS X Version 10.9 or higher, UNIX, LINUX, as well as other operating systems on request.

Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL 3), 4 fonts (Calibri), 4 fonts (Cambria), 1 Bitmap font, 79 Outline fonts

Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, private print, job storage and job management functionality

Mobile printing support: AirPrint, Mopria, Google Cloud Print compliant, NFC, Direct Wi-Fi (optional), MyPanel and KYOCERA Mobile Print app for iOS and Android

COPY FUNCTIONS

Max. original size: A3/Ledger Continuous copying: 1 – 9,999
Zoom range: 25 – 400 % in 1 % steps

Preset magnification ratios: 5 Reductions/5 Enlargements

Exposure mode: Auto, manual: 16 steps Image adjustments: Text + Photo, Photo, Text, Map, Printed

document

Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, image repeat, page numbering, cover mode. booklet copy, interrupt copy, form overlay, margin shift, auto cassette change, Skip blank page, ID card copy

SCAN FUNCTIONS

Functionality: Scan-to-email, Scan-to-FTP, Scan-to-SMB 3.0, Scan-to-USB Host, Scan-to-box, Network TWAIN, WSD scan

Scan speed: (A4, 300 dpi, Dual Scan) 220 images per minute; (A4, 300 dpi, Simplex Scan) 120 images per minute Scan resolution: 600 × 600 dpi, 400 × 400 dpi, 300 × 300 dpi,

200 × 400 dpi, 200 × 200 dpi, 200 × 100 dpi; 256 greyscales per colour

Max. scan size: A3, Ledger, Banner up to 2,200 mr Original recognition: Text, photo, text + photo, light text/ fine line, optimised for OCR

File types: TIFF, PDF, PDF/A, JPEG, Open XPS, Encrypted PDF. High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u, OOXML

Features: Colour scan, Auto Colour Select, integrated address book, Active Directory support, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once, Blank page skip, Specified colour removal

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3 Modem speed: Max. 33.6 kbps Transmission time: Max. 3 seconds (JBIG)

Scanning speed: 2.0 seconds/sheet or less

Address book: 2,000 entries

Fax resolution: Normal: 200 × 100 dpi, Fine: 200 × 200 dpi. erfine: 200×400 dpi, Ultrafine: 400×400 dpi, 600×600 dpi Maximum original size: A3, Ledger, Banner up to 1,600 mm Compression method: JBIG, MMR, MR, MH

CONSUMABLES

Average continuous toner yield in accordance with

TK-6725 Toner Kit: Microfine toner black for 70,000 pages A4 WT-861 Waste Toner Bottle: 600,000 sheets (in accordance

Staples: SH-12 for DF-7110, SH-10 for BF-730/BF-9100, SH-14 for DF-7130

OPTIONS

Fax System 12 Internet Fax Kit (A) (requires Fax System 12)

DT-730(B) Document Table PF-730(B) Paper feeder: 2 × 500 sheets, 60–256 g/m²;

A5R-305 × 457 mm, folio **PF-740(B) Paper feeder:** $2 \times 1,500$ sheets, A4, 60-256 g/m²;

A4, B5, Letter **PF-7120 Paper feeder:** 3,000 sheets, 60–256 g/m²; A4, B5

PF-7130 Multiside Tray: 1×500 sheets DF-7110 Document finisher: Main tray: max. 4,000 sheets A4

(3,000 sheets with BF-730 attachment), max. $60-300 \, \text{g/m}^2$, max. B5R-305 × 457 mm

Sub-tray: 200 sheets A4, 60–300 g/m², A6R–305 \times 457 mm; Stapling up to 65 sheets A4

DF-7130 Document finisher: Main tray: max. 4,000 sheets A4 (3,000 sheets with BF-9100 attachment), max. 52–300 g/m² max. B5R -305×457 mm; Sub-tray: 200 sheets A4; 52-300 g/m², A6R -305×457 mm, Stapling up to 100 sheets A4

PH-7C/PH-7D Punch unit: for DF-7110/DF-7130, 2-hole/4-hole/ vedish type, 60–256 g/m², A5R–A3

MT-730(B) 7-Bin Mailbox sorter: for DF-7110

BF-730 for DF-7110 Booklet and tri-folding unit: Half folding: 60–256 g/m²; A3, B4, A4R; Booklet: max. 16 sheets (64 pages, 60–90 g/m²); Non-staple folding: max. 5 sheets (60–90 g/m²); Tri-folding: $60-105\,\mathrm{g/m^2}$, A4R; Multi tri-folding: 5 sheets (60-90 g/m²)

BF-9100 for DF-7130 Booklet and tri-folding unit: Half folding: 52–256 g/m²; A3, B4, A4R; Booklet: max. 20 sheets (80 pages, 60–90 g/m²); Non-staple folding: max. 5 sheets (60–90 g/m²); Tri-folding: 5 sheets (60–90 g/m²)

Copy tray (D): upper tray 100 sheets, lower tray 250 sheets USB IC Card Reader + Card Authentication Kit (B):

Supports various authentication card keys.

NK-7120: Numeric keypad

Kevboard Holder 10 UG-33: ThinPrint support

UG-34: Emulation (IBM Proprinter/EPSON LQ-850/Diablo 630) Banner Guide (A): Banner paper feeding guide up to 10 sheets Optional interface:

IB-35: Direct Wi-Fi Interface

IB-50: Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ45)

IB-51: Wireless Lan (802.11b/g/n)

The TASKalfa 7003i incorporates extremely durable components that guarantee efficient and reliable operation, to meet the demanding requirements of busy office environments. The TASKalfa 7003i provides effective productivity and maximum flexibility whilst ensuring minimum impact on the environment. This product is compliant with Energy Star.









KYOCERA Document Solutions Partner

NOVEMBER 2019 DSTASKALFA 7003 I/VER 1.0

KYOCERA Document Solutions Europe B.V. Bloemlaan 4, 2132 NP Hoofddorp, The Netherlands Tel +31 (0) 20-654-0000 - Fax +31 (0) 20-653-1256



kyoceradocumentsolutions.eu