



bizhub 651i

Black & White A3 multifunctional









Giving Shape to Ideas

CUSTOMER BENEFITS



Security

Secure network integration, data encryption, overwrite all data function, and advanced user authentication



Productivity

Reliability, high-speed scanning and printing, combined with powerful finishing functions



Sustainability

Numerous eco features reduce energy consumption and costs



Intuitive operability Operate the bizhub like a

smartphone or tablet with fully customized user interface



Application ecosystem Enhanced efficiency thanks

to Konica Minolta's extensive applications portfolio



Services

Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup

OPTIONS



Voice Guidance

Barcode fonts LK-106

Unicode fonts LK-107

OCR A and B fonts

Document converter pack

ThinPrint® client

Antivirus LK-116



2 CONNECTIVITY

Fax board

х2

Wireless LAN UK-221

USB I/F kit USB I/F kit

ID card reader

Mount kit MK-735

3 OTHERS

Working table

10-Key pad

Security kit SC-509

Replacement SSD EM-908

Keyboard holder KH-102

Convenience Stapler

MEDIA INPUT

1x Universal tray PC-116

2x Universal tray

Large capacity tray PC-417

Large capacity tray Large capacity tray LU-207

Banner tray

MEDIA OUTPUT

Output tray OT-513 Off-line stapler FS-P04

Punch kit for FS-542

Staple finisher FS-539

Booklet finisher FS-539SD

unch kit for FS-539/SD K-524

Staple finisher FS-540

Booklet finisher FS-540SD Relay unit RU-513

Punch kit for FS-540/SD PK-526

Post inserter for FS-540/SD PI-507

Job separator for FS-540/SD

Z-fold unit for FS-540/SD

LEGEND

Mandatory option

Option

This option can only be installed with the respective option above it

FINISHING FUNCTIONALITIES

















Half-fold

















stapling

stapling

punching

punching

Duplex

Combined mixplex/ mixmedia

insertion

Tri-fold

Booklet

Offset sorting

printing

Stapling

DESCRIPTION

ENHANCED FEATURES	
LK-104v3 Voice Guidance	Provides voice guidance in select screens
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint® client	Print data compression for reduced network impact
LK-116 Antivirus	Bitdefender® antivirus provides real time scanning of all
	incoming and outgoing data
CONNECTIVITY	
FK-514 Fax board	Super G3 fax, digital fax functionality
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
ID card reader	Various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader
OTHERS	
WT-506 Working table	Authentication device placement
KP-102 10-Key pad	For use instead of touchscreen
SC-509 Security kit	Copy guard function
EM-908 Replacement SSD	1 TB SSD to increase storage space
CS-2 Convenience Stapler	50 Sheet stapler

OTHERS	
KH-102 Keyboard holder	To place USB keyboard
CS-2 Convenience Stapler	50 Sheet stapler
MEDIA INPUT	
IM-103 Intelligent media sensor	Detects paper type and weight automatically
PC-116 1x Universal tray	500 sheets, 5.5" x 8.5" – 11" x 17" / 52–256 g/m 2
PC-216 2x Universal tray	2x500 sheets, $5.5"x8.5"-11"x17"/52-256$ g/m²
PC-416 Large capacity tray	2,500 sheets, 8.5" x 11" / 52–256 g/m ²
PC-417 Large capacity tray	1,500 + 1,000 sheets, 5.5" x 8.5" or 8.5" x 11" $/$ 52–256 g/m 2
LU-302 Large capacity tray	3,000 sheets, 8.5" x 11" / 52–256 g/m ²
LU-207 Large capacity tray	2,500 sheets, 8.5" x 11" – 12" x 18" / 52–256 g/m²
MK-730 Banner tray	Multipage banner feeding
MEDIA OUTPUT	
OT-513 Output tray	Output tray used instead of finisher
OT-513 Output tray FS-542 Inner Finisher	Output tray used instead of finisher 50-Sheet stapling, 500 sheets max. output
FS-542 Inner Finisher	50-Sheet stapling, 500 sheets max. output
FS-542 Inner Finisher PK-527 Punch kit for FS-542	50-Sheet stapling, 500 sheets max. output 2/3 hole punching, auto switching
FS-542 Inner Finisher PK-527 Punch kit for FS-542 FS-539 Staple finisher	50-Sheet stapling, 500 sheets max. output 2/3 hole punching, auto switching 50-sheet stapling; 3,200 sheets max. output
FS-542 Inner Finisher PK-527 Punch kit for FS-542 FS-539 Staple finisher	50-Sheet stapling, 500 sheets max. output 2/3 hole punching, auto switching 50-sheet stapling; 3,200 sheets max. output 50-sheet stapling; 20 sheets booklet finisher;
FS-542 Inner Finisher PK-527 Punch kit for FS-542 FS-539 Staple finisher FS-539SD Booklet finisher	50-Sheet stapling, 500 sheets max. output 2/3 hole punching, auto switching 50-sheet stapling; 3,200 sheets max. output 50-sheet stapling; 20 sheets booklet finisher; 2,200 sheets max. output
FS-542 Inner Finisher PK-527 Punch kit for FS-542 FS-539 Staple finisher FS-539SD Booklet finisher PK-524 Punch kit for FS-539/SD	50-Sheet stapling, 500 sheets max. output 2/3 hole punching, auto switching 50-sheet stapling; 3,200 sheets max. output 50-sheet stapling; 20 sheets booklet finisher; 2,200 sheets max. output 2/3-hole punching; auto switching
FS-542 Inner Finisher PK-527 Punch kit for FS-542 FS-539 Staple finisher FS-539SD Booklet finisher PK-524 Punch kit for FS-539/SD FS-540 Staple finisher	50-Sheet stapling, 500 sheets max. output 2/3 hole punching, auto switching 50-sheet stapling; 3,200 sheets max. output 50-sheet stapling; 20 sheets booklet finisher; 2,200 sheets max. output 2/3-hole punching; auto switching 100-sheet stapling; 3,200 sheets max. output
FS-542 Inner Finisher PK-527 Punch kit for FS-542 FS-539 Staple finisher FS-539SD Booklet finisher PK-524 Punch kit for FS-539/SD FS-540 Staple finisher	50-Sheet stapling, 500 sheets max. output 2/3 hole punching, auto switching 50-sheet stapling; 3,200 sheets max. output 50-sheet stapling; 20 sheets booklet finisher; 2,200 sheets max. output 2/3-hole punching; auto switching 100-sheet stapling; 3,200 sheets max. output 100-sheet stapling; 20 sheets booklet finisher;
FS-542 Inner Finisher PK-527 Punch kit for FS-542 FS-539 Staple finisher FS-539SD Booklet finisher PK-524 Punch kit for FS-539/SD FS-540 Staple finisher FS-540SD Booklet finisher	50-Sheet stapling, 500 sheets max. output 2/3 hole punching, auto switching 50-sheet stapling; 3,200 sheets max. output 50-sheet stapling; 20 sheets booklet finisher; 2,200 sheets max. output 2/3-hole punching; auto switching 100-sheet stapling; 3,200 sheets max. output 100-sheet stapling; 20 sheets booklet finisher; 2,700 sheets max. output
FS-542 Inner Finisher PK-527 Punch kit for FS-542 FS-539 Staple finisher FS-539SD Booklet finisher PK-524 Punch kit for FS-539/SD FS-540 Staple finisher FS-540SD Booklet finisher PK-526 Punch kit for FS-540/SD	50-Sheet stapling, 500 sheets max. output 2/3 hole punching, auto switching 50-sheet stapling; 3,200 sheets max. output 50-sheet stapling; 20 sheets booklet finisher; 2,200 sheets max. output 2/3-hole punching; auto switching 100-sheet stapling; 3,200 sheets max. output 100-sheet stapling; 20 sheets booklet finisher; 2,700 sheets max. output 2/3-hole punching; auto switching
FS-542 Inner Finisher PK-527 Punch kit for FS-542 FS-539 Staple finisher FS-539SD Booklet finisher PK-524 Punch kit for FS-539/SD FS-540 Staple finisher FS-540SD Booklet finisher PK-526 Punch kit for FS-540/SD RU-513 Relay unit	50-Sheet stapling, 500 sheets max. output 2/3 hole punching, auto switching 50-sheet stapling; 3,200 sheets max. output 50-sheet stapling; 20 sheets booklet finisher; 2,200 sheets max. output 2/3-hole punching; auto switching 100-sheet stapling; 3,200 sheets max. output 100-sheet stapling; 20 sheets booklet finisher; 2,700 sheets max. output 2/3-hole punching; auto switching For FS-539/SD or FS-540/SD installation

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

System speed 8.5" x11"	Up to 65 ppm
System speed 11" x 17"	Up to 32 ppm
Autoduplex speed 8.5" x11"	Up to 65 ppm
1st page out time 8.5" x11"	2.8 sec.
Warm-up time	Approx. 15 sec. ¹
Imaging technology	Laser
Toner technology	Simitri® HD polymerized toner
Panel size/resolution	10.1" / 1024 x 600
System memory	8 GB (standard/max)
System hard drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP(S)
Automatic document feeder	Up to 300 originals / 5.5" x 8.5" – 11" x 17" /
	35–210 g/m² / Dual scan ADF
ADF double feed detection	Standard
Printable paper size	3.5" x 5.5" – 12" x 18" / customized paper sizes /
	banner paper max. 47.25" x 11.7"
Printable paper weight	52-300 g/m ²
Paper input capacity	1,150 sheets / 6,650 sheets (standard/max)
Paper tray input (standard)	$1 \times 500 / 3.5$ " x 5.5 " – 11 " x 17 " / custom sizes / 52 – $256 g/m^2$
	1 x 500 / 5.5" x 8.5" – 12" x 18" / custom sizes / 52–256 g/m²
Manual bypass (standard)	150 sheets / 3.5" x 5.5" – 12" x 18" / custom sizes /
	banner / 60-300 g/m ²

SYSTEM SPECIFICATIONS

SYSTEM SPECIFICATIONS	
Paper tray input (optional)	1 x 500 / 5.5" x 8.5" - 11" x 17" / 52-256 g/m ²
	$2 \times 500 / 5.5$ " x 8.5 " – 11 " x 17 "/ 52 – 256 g/m^2
	1 x 2,500 / 8.5" x 11" /52-256 g/m ²
	1 x 1,500 + 1 x 1,000 sheets / 5.5" x 8.5" or 8.5" x 11"/
	52–256 g/m ²
Large capacity tray (optional)	1 x 3,000 / 8.5" x 11" / 52-256 g/m ²
	1 x 2,500/8.5" x 11" – 12" x 18" / custom sizes /
	52-256 g/m ²
Finishing modes (optional)	Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold;
	Letter-fold; Booklet; Post insertion; Z-fold
Automatic duplexing	4.1" x 5.5" – 12" x 18" / 52–256 g/m ²
Output capacity	Up to 250 sheets / up to 3,300 sheets (standard/max)
Stapling	Max. 100 sheets or 98 sheets + 2 cover sheets (up to 300 g/m²)
Stapling output capacity	Max. 200 sets
Tri-fold	Max. 3 sheets
Tri-fold capacity	Max. 50 sets; unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to 300 g/m²)
Booklet output capacity	Max. 35 booklets; unlimited (without tray)
Duty cycle (monthly)	Rec. 53,000 pages; Max. ² 200,000 pages
Toner lifetime	Black up to 24,000 pages
Imaging unit lifetime	Black up to 240,000/1,000,000 pages (drum/developer)
Power consumption	110-120 V / 60 Hz, Less than 1.6 kW

bizhub 651i Datasheet

SYSTEM SPECIFICATIONS

System dimension (W x D x H)	24.2" x 27.1" x 37.8" (without options)
System weight	Approx. 220 lb (without options)
PRINTER SPECIFICATIONS	
Print recolution	1 800 (aquiyalant) v 600 dni: 1200 v 1200 dni

T INTITIENT E CONTONIO	
Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Page description language	PostScript 3 (CPSI 3016); PCL 6 (XL3.0); PCL 5c; XPS
Operating systems	Windows 10 (32/64); Windows 11; Windows Server 2016;
	Windows Server 2019; Windows Server 2022;
	macOS 11 or later; Unix; Linux; Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	Konica Minolta Print Service (Android);
	Konica Minolta Mobile Print (iOS/Android);
	AirPrint (iOS; Mopria (Android)
	optional: Wi-Fi Direct

SCANNER SPECIFICATIONS

SCANNER SPECIFICATIONS	
Scan speed	Up to 140 ipm in simplex (mono)
	Up to 280 ipm in duplex (mono)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV;
	Scan-to-DPWS; Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; PPTX
	optional: Searchable PDF; PDF/A 1a and 1b;
	Searchable DOCX/PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups; LDAP support

COPIER SPECIFICATIONS

Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1–9,999
Original format	Max. 11" x 17"
Magnification	25-400% in 0.1% steps; Auto-zooming

FAX SPECIFCIATION

TAK SI ESII SIATIST	
Fax standard	Super G3 (optional)
Fax transmission	Analog; i-Fax; Color i-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,000 single + 100 groups

























For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication);
	Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling
SYSTEM FEATURES	
Security	ISO 15408 HCD-PP Common Criteria;
	IP filtering and port blocking; SSL3 and TLS1.0/1.1/1.2 network
	communication; IPsec support; IEEE 802.1x support;
	User authentication; Authentication log; Secure print; Kerberos;
	Overwrite all data function; SSD Self-Encryption (AES 256)/
	Storage lock password; Confidential fax;
	Print user data encryption
Security function (optional)	Antivirus realtime scanning (Bitdefender®);
	Copy protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts; Active Directory support (user name +
	password + e-mail + smb folder); User function access definition;
	Authentication by mobile device (Android)
	ID card authentication (ID card reader);
	Authentication by mobile device (iOS)
Software	Net Care Device Manager; Data Administrator; Web Connection;
	Log Management Utility

- All specifications refer to 8.5" x 11" paper of 80 g/m² weight.
 The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a
 particular page size (5% coverage of 8.5" x 11"). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient $temperature \ and \ humidity.$
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

¹ Warm-up time may vary depending on the operating environment and usage

² If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed